


81 K Tragfähigkeit bzw. Lastkurven

81 K Ausleger horizontal,
Kraufbau mit max. 5 Turmstücken



Ausladung (m)	Traglast (kg)			Ausladung (m)	Traglast (kg)			
45,00	1400			26,00	2760	2950	3250	3550
44,00	1440			25,00	2890	3090	3400	3710
43,00	1490			24,00	3030	3240	3560	3890
42,00	1530	1650		23,00	3180	3410	3740	4080
41,00	1580	1700		22,00	3350	3590	3930	4290
40,00	1630	1750		21,00	3540	3790	4150	4520
39,00	1680	1810		20,00	3750	4010	4380	4770
38,00	1740	1870		19,00	3980	4250	4640	5050
37,00	1800	1930	2150	18,00	4230	4520	4930	5370
36,00	1860	2000	2220	17,00	4520	4830	5260	5720
35,00	1920	2070	2300	16,00	4850	5180	5630	6000
34,00	1990	2140	2380	15,00	5220	5570	6000	6000
33,00	2070	2220	2460	14,00	5660	6000	6000	6000
32,00	2150	2310	2550	13,00	6000	6000	6000	6000
31,00	2230	2400	2650	12,00	6000	6000	6000	6000
30,00	2320	2490	2760	11,00	6000	6000	6000	6000
29,00	2420	2590	2870	10,00	6000	6000	6000	6000
28,00	2520	2700	2990	9,00	6000	6000	6000	6000
27,00	2640	2820	3110	8,00	6000	6000	6000	6000
Knickpunkt:					13,3 m	14,1 m	15,1 m	16,3 m

